



XI'AN FUNCTION MATERIAL GROUP CO., LTD  
Safety Data Sheet  
Magnesium Silicon oxide

---

### 1. Product and Company Identification

---

Trade Name: Magnesium Silicon Oxide  
Chemical Formula: MgSiO<sub>3</sub>  
Recommended Use: Scientific research and development

Manufacturer/Supplier: XI'AN FUNCTION MATERIAL GROUP CO., LTD  
Street: No. 69, Gazelle Valley, High-Tech Zone  
City: XIAN  
State: SHAANXI  
Zip Code: 710077  
Country: CHINA  
Tel #: +86-29-88993870/+86-13519132051

---

### 2. Hazards Identification

---

Signal Word: Warning



Hazard Statements: H332: Harmful if inhaled

Precautionary Statements: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P271: Use only outdoors or in a well-ventilated area  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
P312: Call a POISON CENTER or doctor/physician if you feel unwell

HMIS Health Ratings (0-4):

Health: 1  
Flammability: 1  
Physical: 1

---

### 3. Composition

---

Chemical Family: Ceramic  
Additional Names: Magnesium silicate, magnesium metasilicate

Magnesium silicate (Mg<sub>2</sub>SiO<sub>4</sub>):  
Percentage: 100 wt%  
CAS #: 1343-88-0  
EC #: 215-681-1

---

#### 4. First Aid Procedures

---

General Treatment:	Seek medical attention if symptoms persist.
Special Treatment:	None
Important Symptoms:	None
Inhalation:	Remove victim to fresh air. Supply oxygen if breathing is difficult.
Ingestion:	Seek Medical Attention.
Skin:	Wash affected area with mild soap and water. Remove any contaminated clothing.
Eyes:	Flush eyes with water, blinking often for several minutes. Remove contact lenses if present and easy to do. Continue rinsing

---

#### 5. Firefighting Measures

---

Flammability:	Non-flammable
Extinguishing Media:	No special restrictions – use suitable extinguishing agent for surrounding material and type of fire.
Spec. Fire Fighting Procedure:	Use full-face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. See section 10 for decomposition products.

---

#### 6. Accidental Release Measures

---

If Material Is Released/Spilled:	Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust.
Environmental Precautions:	Isolate runoff to prevent environmental pollution.

---

#### 7. Handling and Storage

---

Handling Conditions:	Wash thoroughly after handling.
Storage Conditions:	Store in a cool dry place in a tightly sealed container. Store apart from materials and conditions listed in section 10.
Work/Hygienic Maintenance:	Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.
Ventilation:	Provide sufficient ventilation to maintain concentration at or below threshold limit.

---

#### 8. Exposure Controls and Personal Protection

---

Permissible Exposure Limits:	N/A
Threshold Limit Value:	N/A
Special Equipment:	None
Respiratory Protection:	Dust Respirator
Protective Gloves:	Rubber gloves
Eye Protection:	Safety glasses or goggles
Body Protection:	Protective work clothing. Wear close-toed shoes and long sleeves/pants.

---

## 9. Physical and Chemical Characteristics

---

Color	White
Form:	Powder, Granules, Pellets, Sputtering target, Custom parts
Odor:	Odorless
Water Solubility:	Insoluble
Boiling Point:	N/A
Melting Point:	1910 °C
Flash Point:	N/A
Autoignition Temperature:	N/A
Density:	N/A
Molecular weight:	140.71 g/mol

---

## 10. Reactivity

---

Stability:	Stable under recommended storage conditions
Reacts With:	Oxidizing agents
Incompatible Conditions:	None
Hazardous Decomposition Products:	Magnesium oxide, Silicon oxide

---

## 11. Toxicological Information

---

### Potential Health Effects:

Eyes:	Causes irritation
Skin:	Causes irritation
Ingestion:	May cause irritation
Inhalation:	Harmful
Chronic:	Inhalation of magnesium compounds may cause metal fume fever. Metallic magnesium which perforates the skin may cause local lesions. Some magnesium salts have produced muscle weakness, cardiac arrhythmias, respiratory effects and changes in blood chemistry following ingestion. Inorganic silicon compounds may be acute inhalation irritants. Prolonged inhalation may cause pulmonary fibrosis known as silicosis.

Signs & Symptoms:	N/A
Aggravated Medical Conditions:	N/A
Median Lethal Dose:	N/A
Carcinogen:	N/A

---

## 12. Ecological Information

---

Aquatic Toxicity:	Low
Persistent Bioaccumulation Toxicity:	No
Very Persistent, Very Bioaccumulative:	No
Notes:	N/A

---

## 13. Disposal Considerations

---

Dispose of in accordance with local, state, national, and international regulations.

---

#### 14. Transportation Data

---

Hazardous:	Not hazardous for transportation.
Hazard Class:	N/A
Packing Group:	N/A
UN Number:	N/A
Proper Shipping Name:	N/A

---

#### 15. Regulatory Information

---

Sec 302 Extremely Hazardous:	No
Sec 304 Reportable Quantities:	N/A
Sec 313 Toxic Chemicals:	No

---

#### 16. Other Information

---

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised: 07/13/2019

UNCMATL